## BLF-1240AS : 12V, 40Ah LFP Battery by Bioenno



#### Price: CAD \$539.00

#### **SKU**: BBBLF1240A-1

Product Categories: Multi-Use : 12V, 20-99AHr, Batteries, Lithium, Shop Product Tags: 1240a, 1240AS, 12v, 12v lithium, 40ahr, bioenno, bioenno blf-1240a, bioenno blf-1240as, blf, blf-1240a, blf-1240a canada, blf-1240as, blf1240a, canada, ham, lfp, lfp battery, lifepo4, lithium

#### Product Page:

https://www.modernoutpost.com/product/blf-1240as-12v-40ah-lfp-battery-by-bioen no/

#### **Product Summary**

The BLF-1240AS, 12V, 40Ah LFP Battery by Bioenno is a state-of-the-art 12V 40Ah battery. This is a staple of Bioenno Power's high-power 12V battery line designed for more stationary applications and higher power consumption portable electronics requiring a higher capacity and greater power output battery while demanding a battery which can reliably provide excellent performance over an extended service life.

### Product Description

The BLF-1240AS, 12V, 40Ah LFP Battery by Bioenno is a state-of-the-art 12V 40Ah battery. This is a staple of Bioenno Power's high-power 12V battery line designed for more stationary applications and higher power consumption portable electronics requiring a higher capacity and greater power output battery while demanding a battery which can reliably provide excellent performance over an extended service life.

#### Best Solar Options Boulder 100 FSP 60 FSP 110 DuraLite 100

\*Use a lithium solar charge controller with this module on bare LFP batteries... <u>Genasun GV-5-Li-14.2</u> <u>Powerwerx MPPT-150</u>

The BLF-1240AS battery has an integrated PCM (protection circuit module) which provides complete internal cell balancing, complete integrated protection along with integrated charge circuitry and boasts no EMI/RFI (Electromagnetic Interference/Radio-Frequency Interference) and is absolutely quiet! This unit has an available 110VAC/220 VAC AC-to-DC charger, that provides 6A, with a Powerpole connector. Please note that this battery should be charged using a LiFePO4 compatible charger, and not with a charger for SLA batteries.

# BLF-1240AS User Manual [PDF BLF-1240AS Battery Specifications

Voltage: 12V

Capacity: 40Ah

Case Type: ABS Sealed

Charge/Discharge Connector: Terminal bolts

Maximum Continuous Discharge Current: 40A

Maximum Peak Discharge Current: 80A (5 sec)

Max Power Delivered to Load @ 12V: 480 Watts (12V x 40A = 480 Watts)

Dimensions:(L x W x H) 8.8 in. x 3.8 in. x 6.9 in. (223 mm x 95 mm x 175 mm) Weight: 10.4 lbs. (4.7 kg.)

Includes built-in PCM (protection circuit module) which provides internal cell balancing and management, protection from overcurrent, undervoltage (overdischarge), overvoltage and short circuiting, and has integrated charging circuitry Available 110VAC / 220 VAC Charger **Recommended AC-to-DC Charger Specifications (not included)** Input Voltage: 110VAC/120VAC Output Voltage: 14.6VDC Current: 6A Connector: Anderson Powerpole Model Number: <u>BPC-1506A</u>]

Warranty: 2 Years

**Product Attributes** 

- Dimensions: 1 × 1 × 1 cm
- Weight: 5 kg