

BMV-700 : Battery Monitor from Victron Energy



Price: CAD \$155.00

SKU: VEBMV700

Product Categories: [Meters](#), [Shop](#), [Wiring & BOS](#)

Product Tags: [bmv-700](#), [bmv-700 battery monitor](#), [bmv-700 canada](#), [bmv700, canada](#), [victron battery monitor](#), [victron bmv-700](#), [victron energy](#)

Product Page:

<https://www.modernoutpost.com/product/bmv-700-battery-monitor-from-victron-energy/>

Product Summary

The BMV-700 is a high precision battery monitor. The essential function of a battery monitor is to calculate ampere hours consumed and the state of charge of a battery. Ampere hours consumed are calculated by integrating the current flowing in or out of the battery.

Product Description

The BMV-700 is a high precision battery monitor. The essential function of a battery monitor is to calculate ampere hours consumed and the state of charge of a battery. Ampere hours consumed are calculated by integrating the current flowing in or out of the battery.

To read more about the full BMV range & accessories, see this [blog](#).

BMV-700 Standard Features

- Battery voltage, current, power, ampere-hours consumed and state of charge
- Remaining time at the current rate of discharge
- Programmable visual and audible alarm
- Programmable relay, to turn off non critical loads or to run a generator when needed
- 500 Amp quick connect shunt and connection kit
- Shunt selection capability up to 10.000 Amps
- VE.Direct communication port
- Stores a wide range of historical events, which can be used to evaluate usage patterns and battery health
- Wide input voltage range: 6,5 - 95V
- High current measurement resolution: 10 mA (0,01A)
- Low current consumption: 2,9Ah per month (4mA) @12V and 2,2Ah per month (3mA) @ 24V

About the BMV-700 Battery Monitor

Battery 'fuel gauge', time-to-go indicator, and much more

The remaining battery capacity depends on the ampere-hours consumed, discharge current, temperature and the age of the battery. Complex software algorithms are needed to take all these variables into account. Next to the basic display options, such as voltage, current and ampere-hours consumed, the BMV-700 series also displays state of charge, time to go, and power consumption in Watts. The BMV-702 features an additional input which can be programmed to measure the voltage (of a

second battery), battery temperature or midpoint voltage (see below).

Bluetooth Smart

Use the **Victron Bluetooth Smart dongle** to monitor your batteries on Apple or Android smartphones, tablets, macbooks and other devices.

Easy to install

All electrical connections are to the quick connect PCB on the current shunt. The shunt connects to the monitor with a standard RJ12 telephone cable. Included: RJ 12 cable (10 m) and battery cable with fuse (2 m); no other components needed. Also included are a separate front bezel for a square or round display appearance, a securing ring for the rear mounting and screws for the front mounting.

Easy to program (with your smartphone!)

A quick install menu and a detailed setup menu with scrolling texts assist the user when going through the various settings. Alternatively, choose the fast and easy solution: download the smartphone app (Bluetooth Smart dongle needed)

Download BMV-700 Documentation

[Download the Spec Sheet](#)] [Download the Quick Installation Guide](#)] [Download the User Manual](#)]

Product Attributes

- Dimensions: 1 × 1 × 1 cm
- Weight: .9 kg