

Cerbo GX : System Communication Hub by Victron



Price: CAD \$339.00

SKU: VE-CERBO-GX

Product Categories: [Battery Installation](#), [Battery Monitors](#), [CC Accessories](#), [Inverter Installation](#), [Meters](#), [Remotes & Displays](#), [Shop](#), [Wiring & BOS](#)

Product Tags: [BPP900450100](#), [canada](#), [cerbo](#), [cerbo gx](#), [cerbo gx canada](#), [communication](#), [Gateway](#), [Hub](#), [victron cerbo gx](#)

Product Page:

<https://www.modernoutpost.com/product/cerbo-gx-system-communication-hub-by-victron/>

Product Summary

The Cerbo GX communication-centre allows you to always have perfect control over your system from wherever you are and to maximize its performance. Simply access your system via our Victron Remote Management (VRM) portal, or access it

directly, using the optional [GX Touch 50](#)] screen, a Multi-Functional Display (MFD) or our VictronConnect app thanks to its Bluetooth capability.

Product Description

The Cerbo GX communication-centre allows you to always have perfect control over your system from wherever you are and to maximize its performance. Simply access your system via our Victron Remote Management (VRM) portal, or access it directly, using the optional [GX Touch 50](#)] screen, a Multi-Functional Display (MFD) or our VictronConnect app thanks to its Bluetooth capability.

Cerbo GX Facilitates Monitoring & Control

Instantly monitor the battery state of charge, power consumption, power harvest from PV, generator, and mains, or check tank levels and temperature measurements. Easily control the shore power input current limit, (auto)start/stop generator(s) or change any setting to optimise the system. Follow up on alerts, perform diagnostic checks and resolve complications remotely.

Cerbo GX Data on Remote VRM Console

Monitor, control and configure the Cerbo GX remotely, over the internet. Just like if you were standing in front of the device, using Remote Console. The same functionality is also available on the local network LAN, or using the WiFi Access Point of the Cerbo GX.

Cerbo GX Mounting and Configuration

The Cerbo GX is easily mountable and can also be mounted on a DIN-Rail using the DIN35 adapter small, (not included). Its separate touchscreen can be bolted on a dashboard, eliminating the need to create perfect cutouts (like with the Color Control GX). Connection is easy via just one cable, taking away the hassle of having to bring many wires to the dashboard. The Bluetooth feature enables a quick connection and configuration via our VictronConnect app.

Cerbo GX Specifications

Part# : BPP900450100

Supply voltage : 8 - 70V DC

Mounting : Wall or DIN rail (35mm)

Communication ports :

+ VE.Direct ports (always isolated) : 3

+ VE.Bus (always isolated) : 2 paralleled RJ45 sockets

+ VE.Can : Yes - non isolated

Outer dimensions (h x w x d) : 7.8 x 15.4 x 4.8 cm

Operating temperature range : -20 to +50°C

Download the Spec Sheet and User manuals

Product Attributes

- Dimensions: 18 × 10 × 6 cm
- Weight: 1.2 kg

Product Gallery





