

Classic 150 MPPT Charge Controller



Price: CAD \$1,179.00

SKU: MNCLASSIC150

Product Categories: [Charge Controllers](#), [MPPT : 60A-100A](#), [Shop](#)

Product Tags: [150V](#), [canada](#), [classic](#), [classic 150](#), [classic 150 canada](#), [midnite canada](#), [midnite classic 150](#), [MPPT](#), [mppt charge controller](#), [mppt solar](#), [solar charge controller](#), [solar controller](#)

Product Page:

<https://www.modernoutpost.com/product/classic-150-mppt-charge-controller/>

Product Summary

MidNite Solar's iconic and best selling MPPT solar charge controller, the Classic 150 extends the features, flexibility, & range of MPPT solar charge controllers. The Classic 150 MPPT Charge Controller has Arc Fault, Ground Fault, free web monitoring, a graphics panel and Solar, Hydro and Wind Modes.

Product Description

MidNite Solar's iconic and best selling Classic 150 MPPT solar charge controller, extends the features, flexibility, & range of MPPT solar charge controllers. The Classic MPPT Charge Controller has Arc Fault, Ground Fault, free web monitoring, a graphics panel and Solar, Hydro and Wind Modes.

The Classic 150 has a maximum output current of 96 amps, an operating voltage of 150 volts and works with 12 to 72 volt battery systems. The FREE MidNite Solar Local Application enables you to monitor your Classics over your local network or the Internet. As with the whole Classic Line, the 150 has MidNite's exclusive HyperVOC which extends VOC limits when needed.

MidNite Classic 150 MPPT Features...

- Manual & auto EQ - Built-in DC-GFP & Arc Fault Protection - Communicates with the Clipper & Whizbang Jr - Mymidnite.com online status monitoring - Full internet capability - Remote & local displays possible - 150VDC operating voltage - Exclusive hyperVOC extends VOC limits - 380 days of daily history, 24hrs of data @ 5 min intervals - 12-72V battery charging standard - Solar, Wind, & Hydro MPPT modes - Ethernet, Modbus, & RS232 communications - Parallel operation for multiple Classic systems - ETL listed to UL1741 & CSA for the US & Canada - Max current out: 96 amps - ETL listed to UL1741 and CSA - Type 1 environmental rating - Terminals are rated for 75 C - 5-Year warranty - Made in the USA [Download the brochure](#)]

Product Attributes

- Dimensions: 1 × 1 × 1 cm
- Weight: 1.4 kg