D224NRB: 200A, 240VAC General-Duty Safety Switch Disconnect



Price: CAD \$1,399.00

SKU: SCH D224NRB

Product Categories: Disconnects, Shop, Wiring & BOS

Product Tags: 200A, 200a switch, canada, d224nrb, d224nrb canada, disconnect, enphase, safety, service disconnect,

square-d, square-d d224nrb, switch

Product Page: https://www.modernoutpost.com/product/d224nrb-200a-240vac-general-duty-safety-switch-disconnect/

Product Summary

The Square-D D224NRB. A 200A, 240VAC general-duty safety switch disconnect designed for residential and commercial applications where durability and economy are prime considerations. Typical loads include lighting, air conditioning, and appliances. They are suitable for use as service equipment when equipped with a factory installed neutral assembly or field installed service grounding kit.

Product Description

The Square-D D224NRB. A 200A, 240VAC general-duty safety switch disconnect designed for residential and commercial applications where durability and economy are prime considerations. Typical loads include lighting, air conditioning, and appliances. They are suitable for use as service equipment when equipped with a factory installed neutral assembly or field installed service grounding kit.

This general duty single throw safety switch is a two pole, 200A, fusible disconnect with a 240VAC voltage rating. This switch has a factory installed neutral and a NEMA 3R enclosure and is surface mounted. This safety switch accepts H, K, or R fuses. This switch comes with lugs suitable for aluminum or copper conductors. This safety switch accepts H, K,

or R fuses. These general duty switches are UL listed.

*Note:

Enphase System Controllers are not approved as service entrance equipment in Canada (see the spec sheet for more information). Therefore, the D224NRB can provide this functionality.

This unit has been replaced by the 3-Pole <u>D324NRB</u>] model. Use 2 poles for single phase, all three poles for 3-phase. D224NRB Switch Features

General duty fusible 200A, 240VAC safety switch for residential and commercial applications

Type 3R enclosure for rainproof applications, with bolt on hub provision

Excellent for disconnecting lighting, air condition, and appliances

Suitable for service entrance when equipped with neutral assembly or equipment grounding kit

Factory installed neutral

Download D224NRB Documentation Product Datasheet Instruction Sheet

Product Attributes

- Dimensions: 85 × 50 × 26 cm

- Weight: 14 kg