

# GP-PV-10M : 10W Monocrystalline Solar Module by Go Power



**Price: CAD \$49.99**

**SKU:** GP-PV-10M

**Product Categories:** [Crystalline](#), [Portable / Luggable](#), [Roof / Ground / Pole](#), [Shop](#), [Small Modules : 10W+](#), [Solar Modules](#)

**Product Tags:** [10 watt](#), [10w](#), [10w solar module](#), [10W Solar Panel](#), [go power GP-PV-10M](#), [GP-PV-10M](#), [GP-PV-10M canada](#), [mono](#), [small solar](#), [solar trickle charge](#)

**Product Page:** <https://www.modernoutpost.com/product/gp-pv-10m-10w-monocrystalline-solar-module-by-go-power/>

## Product Summary

The GP-PV-10M Solar Module from Go Power! is a high efficiency polycrystalline solar module that provides outstanding performance and cost-effective solar power for many types of applications. The module is built to last, and features a 25-year limited power output warranty.

## Product Description

The GP-PV-10M Solar Module from Go Power! is a high efficiency monocrystalline solar module that provides outstanding performance and cost-effective solar power for many types of applications. The module is built to last, and features a 25-year limited power output warranty.

To ensure long life, the high-efficiency solar cells are encapsulated between a special tempered, low-iron solar glass and a tedlar/polyester backing material. The mounting frame, manufactured from anodized marine grade aluminum, allows the GP-PV-10M to be installed in extreme conditions. A conduit ready junction box is compatible with a wide range of cable and conduit types.

**GP-PV-10M Features**

- Compact and rugged design - Plug and play junction box - Dual positive / negative bare wire connectors - Lightweight anodized aluminum frame - High transmissivity tempered glass - 7m Cable with built-in fuse - Junction Box with bypass and blocking diodes

### GP-PV-10M Specifications

Solar cell type : Monocrystalline

Output power : 10W

Rated current : 0.57A

Rated DC voltage : 17.5V

Open-circuit voltage : 21V

Module efficiency : 17.30%

Connectivity : MC4 connectors

Frame type : Clear anodized aluminum frame

Maximum System Voltage : 600VDC

Dimensions : 13.19 x 9.25 x 0.98 in / 335 x 235 x 25 mm

Weight : 1.76 lb (0.8 kg)

Warranty : 25 years power output (module)

Downloads

[Spec Sheet](#)

## Product Attributes

- Dimensions: 1 &times; 1 &times; 1 cm
- Weight: 1.4 kg

## Product Gallery

