GP-RVC-DIS-3: PowerTrak Remote Display Screen by Go Power



Price: CAD \$149.99

SKU: GP-RVC-DIS-3

Product Categories: CC Accessories, Charge Controllers, Shop

Product Tags: <u>bluetooth</u>, <u>canada</u>, <u>display screen</u>, <u>go power</u>, <u>GP-RVC-DIS-3</u>, <u>GP-RVC-DIS-3 canada</u>, <u>powertrak</u>, <u>remote</u>, <u>remote display</u>, <u>rvc</u>, <u>screen</u>, <u>touch</u>

Product Page:

https://www.modernoutpost.com/product/gp-rvc-dis-3-powertrak-remote-display-scr een-by-go-power/

Product Summary

This is the GP-RVC-DIS-3, the PowerTrak remote display screen by Go Power. This advanced screen seamlessly combines three controls into a single, user-friendly interface. Enjoy automatic dimming throughout the day, courtesy of the built-in

light sensor, providing a customized and efficient experience. Stay connected with ease using the included connectivity cables, and navigate effortlessly with the touch screen color display. Choose from multiple orientation options for a personalized and versatile control solution.

Product Description

This is the GP-RVC-DIS-3, the PowerTrak remote display screen by Go Power. This advanced screen seamlessly combines three controls into a single, user-friendly interface. Enjoy automatic dimming throughout the day, courtesy of the built-in light sensor, providing a customized and efficient experience. Stay connected with ease using the included connectivity cables, and navigate effortlessly with the touch screen color display. Choose from multiple orientation options for a personalized and versatile control solution.

GP-RVC-DIS-3 PowerTrak Remote Display Screen Features Combine 3 controls into one screen

Built in light sensor for automatic dimming throughout the day

Comes with connectivity cables

Touch screen color display

Multiple orientation options

Works with the GP-MPPT-30-RVC] solar charge controller.

.

PowerTrak Remote Display Screen Specifications

Display Size: 3.2 inches

Display Resolution: 320×240

Touchscreen: Resistive

Supply Voltage: 12-48 VDC

Max Supply Current...

@ 12 VDC Input - 400 mA

@ 24 VDC Input - 200 mA

Operating Temperature Range : -20 to +50 °C

Storage Temperature Range : -30 to +70 °C

Humidity: 5-95 % RH, non-condensing

Bluetooth Range: 50 meters

WiFi Bandwidth: 2.4 Ghz

LCD Screen: 320×240 resolution

Connectivity: 4 pin, 2mm pitch header connection

Document Downloads

PowerTrak™ Screen Quick Start Guide (GP-RVC-DIS-3) Over the Air Update Guide

Product Attributes

- Dimensions: 24 × 16 × 7 cm

- Weight: .4 kg

Product Gallery

