11 SQF-2 : Grundfos SQFlex Submersible Solar Pump



Price: CAD \$3,939.00

SKU: GF11SQF-2

Product Categories: Appliances, Shop

Product Tags: 11 sqf-2, 11sqf-2, canada, grundfos, grundfos 11 sqf-2, grundfos solar pump, pump, solar pump, solar water pumping, sqflex, water pump, water pumping

Product Page:

https://www.modernoutpost.com/product/grundfos-sqflex-submersible-solar-pump-11-sqf-2/

Product Summary

This is the Grundfos SQFlex Submersible Solar Pump: 11 SQF-2 Grundfos SQFlex Submersible Pumps offer the basis for a complete off-grid water supply system. Built with flexibility in mind, the 11 SQF-2 pump is able to run efficiently from either AC or DC power, and incorporates a built-in MPPT controller and soft-start. This model is a helical rotor pump, ideal when up to 120m (395') of lift is required, and up to 52 L/min (13 Gal/min).

Product Description

This is the Grundfos SQFlex Submersible Solar Pump: 11 SQF-2

Grundfos SQFlex Submersible Pumps offer the basis for a complete off-grid water supply system. Built with flexibility in mind, the 11 SQF-2 pump is able to run efficiently from either AC or DC power, and incorporates a built-in MPPT controller and soft-start. This model is a helical rotor pump, ideal when up to 120m (395') of lift is required, and up to 52 L/min (13 Gal/min).

When the solar resource is unreliable, the Grundfos SQFlex pumps can be integrated with battery back-up systems.

11 SQF-2 Pump Applications

SQFlex pumps are designed for continuous & intermittent operation, and are ideally suited to...

- Residential : Villages, schools, hospitals, single-family houses, etc. Farms
- : Watering cattle, Irrigation of fields or greenhouses Surface water pumping : Water from ponds and lakes

Grundfos 11 SQF-2 Features

- Runs from either DC or AC power: 30V - 300V - Built-in electronics make for simple installation - Extremely reliable - Low operating costs - Dry-running protection - Built-in motor protection - High efficiency - Built-in maximum power point tracking (MPPT) - Wide voltage range - Built-in sand shield

Grundfos 11 SQF-2 Pump Specifications

- 47" L x 2.9" diameter - 17 lbs - Voltage (DC): 30 - 300V - Voltage (AC): 90 - 240V - Max head/pressure: 395' / 170 psi

Flow Rate:

12.5 gal/min @ 15' (250W Power)

10 gal/min @ 395' (1400W Power)

- Connection: 1" NPT - Stainless steel housing - Model number: 11 SQF-2

Literature Downloads

SQFlex Brochure

SQFlex Product Guide (Includes pump performance curves)

SQFlex Battery Back-Up System]

Product Attributes

- Dimensions: 1 × 1 × 1 cm

- Weight: 10 kg

Product Gallery

