

HC6-420 : HUB Carbon AGM Battery 6V, 420Ah, L16



Price: CAD \$789.00

SKU: HUBHC6-420

Product Categories: [Batteries](#), [Lead-Acid](#), [Sealed : Lead-Carbon](#), [Shop](#)

Product Tags: [420ah](#), [6v](#), [agm](#), [agm battery](#), [canada](#), [carbon](#), [gc2](#), [golf cart](#), [hc6-220](#), [hc6-220 canada](#), [hc6-420](#), [hub hc6-220](#), [hub hc6-420](#), [l16](#), [lead-carbon](#)

Product Page: <https://www.modernoutpost.com/product/hc6-420-hub-carbon-agm-battery-6v-420ah-l16/>

Product Summary

For some applications, Lithium is not the right solution. When it comes to lead-acid AGM batteries, the best chemistry is lead-carbon due to its longevity and tolerance to partial state-of-charge. The HC6-420 lead-carbon battery uses activated carbon and graphene in the manufacturing process. The advantages over standard AGM include long cycle life and significantly reduced battery sulfation.

Product Description

For some applications, Lithium is not the right solution. When it comes to lead-acid AGM batteries, the best chemistry is lead-carbon due to its longevity and tolerance to partial state-of-charge. The HC6-420 lead-carbon battery uses activated carbon and graphene in the manufacturing process. The advantages over standard AGM include long cycle life and significantly reduced battery sulfation.

Lead-Carbon battery technology improves the charge and discharge speed, while greatly prolonging battery life. Expect more than 2,000 cycles at 80 % DOD. The HC series are ideal for cycling and partial state of charge (PSOC) applications like solar.

HC6-420 Applications

- Off Grid Cabins & Homes - Marine / RV - Hybrid Solar & Grid Tie - Wheel Chairs, Golf Carts - Telecom Systems
- Off-Grid Industrial - Micro Grid Systems

HC6-420 Features

- Common size (L16) - Able to operate at -40C to +60C - 3000 cycles @ 50% DoD - Integrated design to ensure the best uniformity and reliability - Long life and high stability in partial state of charge (PSOC) - IEC 60896

HC6-420 Specifications In Brief

ELECTRICAL SPECIFICATIONS

Nominal Voltage : 6V

Amp Hour Capacity C20 : 420Ah

Amp Hour Capacity C100 : 466Ah

CHARGE SPECIFICATIONS

Recommend Charge current : 42A

Max Charge current : 100A

MECHANICAL SPECIFICATIONS

Dimensions (L x W x H) : 295 x 178x 424mm / 12 x 7.1 x 16.7in

BCI# : L16

Weight : 56.8KG / 125 lbs

Terminal Type : Auto/Stud

Cell Type : Lead Carbon VRLA

SAFETY

Safety Ratings : IEC60896, CE

[Document Download](#)

SPEC SHEET

Product Attributes

- Dimensions: 43 × 30 × 18 cm
- Weight: 57 kg