

HUB-12.8V-50-LFP-22NF : 12V, 50Ah Lithium Battery

12V 50AH



Price: CAD \$599.00

SKU: HUB-12.8V-50-LFP-22NF

Product Categories: [Batteries](#), [Lithium](#), [Multi-Use : 12V, 20-99Ahr](#), [Shop](#)

Product Tags: [12.8v](#), [12v](#), [40ah](#), [50ah](#), [600wh](#), [640wh](#), [canada](#), [cold weather lithium](#), [heated lithium](#), [hub power](#), [HUB-12.8V-40-LFP-U1](#), [HUB-12.8V-40-LFP-U1 canada](#), [lfp canada](#), [lifepo4](#), [lifepo4 battery canada](#)

Product Page: <https://www.modernoutpost.com/product/hub-12-8v-50-lfp-22nf-12v-50ah-lithium-battery/>

Product Summary

The HUB-12.8V-50-LFP-22NF is a premium 12V, 50Ah Lithium battery that's ideal for smaller renewable energy projects, emergency power boxes, and portable power stations. Outstanding performance from a Canadian company that's dedicated to performance.

Product Description

The HUB-12.8V-50-LFP-22NF is a premium 12V, 50Ah Lithium battery that's ideal for smaller renewable energy projects, emergency power boxes, and portable power stations. Outstanding performance from a Canadian company that's dedicated to performance.

Hub Power is a Canadian-based company, building their batteries with certified, verified grade A Lithium Iron Phosphate cells. It matters, both for safety, and performance of the battery.

This is why HUB provides a 10-year limited warranty with a 4-year replacement period.

HUB-12.8V-50-LFP-22NF Advantages

Start at the core of what a battery needs to provide

- Prismatic LiFePO4 Lithium Iron Phosphate Grade A cells

- High Reliability
- Fast and Efficient charge/ discharge cycles
- Deep Discharge capability
- Fully Recycle capability
- Light weight
- Environmentally friendly
- UL Approved Cells
- Safety UN38.3 approved
- UN3480, CLASS 9

HUB-12.8V-50-LFP-22NF Specifications in Brief

ELECTRICAL SPECIFICATIONS

Nominal Voltage : 12.8V

Amp Hour Capacity : 50AH

Energy Density : 640Wh

Efficiency - round trip : > 99.5%

Self Discharge per Month : < 3%

**Do not configure series and parallel connections simultaneously

**Max 4 series connections (12 - 48V)

**Max 4 parallel connections 50-200AH (2,560Wh)

CHARGE SPECIFICATIONS

Recommend Charge current 5A - 25A

Max Charge current 50A

DISCHARGE SPECIFICATIONS

Max Cont Discharge current : 50A

Peak Discharge Current 3C : 150A

BMS Current Cut Off (10S) : >52.5A

HEATING CIRCUIT

Operating Range : (-20 to 5C)

MECHANICAL SPECIFICATIONS

Dimensions L x W x H : 229 x 138 x 213mm (9.02 x 5.43 x 8.39in)

Weight : 7.0kg (15.43lbs)

Terminal Type : M6

Download the complete Spec Sheet

Product Attributes

- Dimensions: 23 × 14 × 22 cm
- Weight: 7 kg