KnockOut Tile Replacement Kit by Ironridge



Price: CAD \$29.00 - CAD \$39.99

SKU: IR-KNOCKOUT-TILE

Product Categories: Mounts, Rooftop Attachments, Shop, Tile Roof

Product Tags: canada, flashing, flat, ironridge knockout, ironridge KOF-W01-T1, knock-out, knockout, KOF-F01-T1, KOF-S01-T1, KOF-W01-T1, KOF-W01-T1 canada, mount, s, solar mount for tile, solar tile, tile, tile mount, tile replacement, w

Product Page:

https://www.modernoutpost.com/product/knockout-tile-replacement-kit-by-ironridge

Product Variants

- KnockOut Tile Replacement Kit by Ironridge Flat Flashing ()
- KnockOut Tile Replacement Kit by Ironridge Roof Base Unit ()
- KnockOut Tile Replacement Kit by Ironridge W Curve Flashing ()
- KnockOut Tile Replacement Kit by Ironridge S Curve Flashing ()

Product Summary

This is the KOF-W01-T1 Ironridge's tile replacement flashing mount in 'W' shape format. Solar installations on tile roofs can be difficult and time-consuming. These jobs often necessitate tile grinding to ensure proper fit, a struggle to match mounting components, and extensive searches for broken tile replacements.

Product Description

This is Ironridge's KnockOut tile replacement flashing mount kit featuring 'W' shape flashing. Solar installations on tile roofs can be difficult and time-consuming. These jobs often necessitate tile grinding to ensure proper fit, a struggle to match mounting components, and extensive searches for broken tile replacements. The response is Knockout Tile. The replacement mount fits into the current roof structure quickly and efficiently. You make a solid stack of high-performance, form-fitting components with a hammer strike that fully encases the waterproof seal. As a result, installation time and flexibility have never been better. Various flashing profiles are available...

Flat: KOF-F01-T1 "W": KOF-W01-T1 "S": KOF-S01-T1

KnockOut Tile Replacement Features



Form-Fit Waterproofing

Knockout Tile's unique compression seal technology holds water out and in by connecting the flashing, gasket, and L-foot with a single hammer strike.



Universal Base

Knockout Tile base is solid, but light, and has a small footprint. It can be installed anywhere along the rafter in any orientation. Flat, S, and W flashings all use the universal platform.



Concentric Loading

The use of a single lag with a minimal offset between the lag bold and the L-foot enhances structural efficiency. This leads to a 40% increase in loading capability and a 50% reduction in roof penetrations.



Deck Flashing (optional)

An optional Knockout Tile Deck Flashing is available to add an extra layer of waterproofing, when necessary.

.

Watch the video...

.

UL 2703 Certification



All IronRidge® Systems have been listed to UL 2703, the standard for evaluating solar mounting systems. This ensures they maintain strong electrical and mechanical connections over an extended period of time in extreme outdoor environments.

25-Year Warranty




IronRidge® products come with a 25-year warranty, guaranteeing they will be free of defects in materials and manufacturing which materially impair the use of the products for the purposes for which they were designed.


Knock-Out Tile Replacement Mount Documentation Downloads



KO Tile Tech Brief



KO Tile Install Manual



KO Tile Cut Sheet Deck Flashing Cut Sheet

Product Attributes

- Dimensions: 46 × 36 × 3 cm

- Weight: 1.9 kg

- Parts: Roof Base Unit, Flat Flashing, W Curve Flashing, S Curve Flashing

Product Gallery







