# Midnite MNPV8HV-DISCO 3R String Combiner



Price: CAD \$1,399.00

SKU: MSMNPV8HVDISCO3R-SPECIAL

In stock: 1

Product Categories: Combiners: Solar & Battery, Shop, Wiring & BOS

Product Tags: canada, disconnecting combiner, midnite solar, mnpv8, mnpv8hv,

mnpv8hv disco 3r, string combiner

**Product Page:** 

https://www.modernoutpost.com/product/midnite-mnpv8hv-disco-3r-string-combine r-special/

## **Product Summary**

Special: MNPV8HV-DISCO 3R Midnite String Combiner
MNPV8HV-DISCO 3R PV Disconnecting Combiner, 5 poles, 80 or 160 amp busbars
depending on how they are configured. Switch is a 100 amp load break rated or
175 amps load break rated depending on configuration, 600 volt max.

### **Product Description**

Special: MNPV8HV-DISCO 3R Midnite String Combiner
MNPV8HV-DISCO 3R PV Disconnecting Combiner, 5 poles, 80 or 160 amp busbars
depending on how they are configured. Switch is a 100 amp load break rated or
175 amps load break rated depending on configuration, 600 volt max. (shown with
surge protection device installed - not included)

#### The MNPV8HV-DISCO 3R's red handled is LOCKABLE IN THE OFF POSITION!

- Convertible configuration (field configurable) Eight strings combined for up to 160 Amps single 230 Amp/600V single pole disconnect) 4 + 4 positive strings, separate PV+ and PV- for use with 2 inverters (2 pole 115 Amp disconnect) Four strings positive, four strings minus for use with non-isolated inverters (2 pole 115 Amp disconnect) Disconnect has built in shunt trip with positive feedback <a href="Birdhouse">Birdhouse</a> compatible] Load Break Rated Optional PV connected power supply Optional AC connected power supply for redundancy
- Type 3R aluminum enclosure (no rust, won't turn to dust)

#### 90o C connections

- See thru deadfront & color coded busbar guards included - Fuseholders (

MNTS) installed] - 15a/600v fuses installed - 600 volt max - Meets 2014 NEC 690.12

Warranty - 5 yrs.] - Listed by ETL for US & Canada - Made in the USA Hardware

Includes: - One MNSPD-600 (Surge Protection Device)] - Eight 1/2" strain reliefs (

MNSR-1000)] - Eight 1/2" LOCKNUTS - One 10-32 X 7/8" BOLT - Two 10-32 X 3/8"

FHP - Six 10-32 KEPS NUT - One TERMINAL PIN 18-22 AWG. - One TERMINAL PIN

10-12 AWG. - Two RING TERMINAL 10-12 AWG. - One BUSBAR, NEGATIVE OUT

2 - One BUSBAR, POSITIVE OUT 2 - One BLUE WRENCH]

### **Product Attributes**

- Dimensions: 1 × 1 × 1 cm

- Weight: 10 kg