

Outback Power AXS Port Modbus Interface



Price: CAD \$499.00

SKU: OPAXSPORT

Product Categories: [Cables & Wiring Kits](#), [Inverters](#), [Shop](#)

Product Tags: [axs](#), [axs port](#), [axs port canada](#), [canada](#), [modbus](#), [Monitoring](#), [outback](#), [outback axs port](#), [outback AXS port canada](#), [outback power](#), [port](#)

Product Page:

<https://www.modernoutpost.com/product/outback-power-axs-port-modbus-interface/>

Product Summary

The AXS Port Modbus TCP, now OPTICS RE compatible, is a powerful and economical tool that allows installers and system owners the ability to monitor and control system status from any location.

Product Description

The AXS Port Modbus TCP, now OPTICS RE compatible, is a powerful and economical tool that allows installers and system owners the ability to monitor and control system status from any location.

AXS Port Features

- Remote system control and monitoring via web interface with OPTICS RE - SunSpec-compliant device for interoperability and plug-and-play and operation
- Over two years of data logging - Accessories include MicroSD memory and DIN-rail mounting clip

When paired with OPTICS RE, the AXS Port interface offers advanced monitoring and control features including:

- Real-Time PV/Solar System Performance Monitoring via Intuitive Dashboard Interface From any Internet-Connected Device - Efficient Management of Multiple OutBack Power System Installations Under One Account - Remote Troubleshooting - Reduced Onsite Service Calls and System Downtime

The AXS Port makes it possible to create custom user interfaces for systems using the advanced API program development kit* and download system data logs using Modbus-read or FTP transfer. All user-configurable values are backed up with non-volatile memory, ensuring stable performance and system recovery. An optional remote temperature-sensing function provides a simple, low-cost tool for capturing and reporting ambient temperature or other critical thermal information records.

The AXS Port is a SunSpec compliant device**, which means it speaks the renewable energy industry's common language used to drive data and interoperability standards for plug-and-play operation between components and management systems.

AXS Port Documentation Downloads

Datasheet : [AXS Port Datasheet](#)

Manual : [AXS Port - Technical Documentation](#)

Product Attributes

- Dimensions: 1 × 1 × 1 cm
- Weight: .9 kg