RB40: 40Ahr, 12V Lithium Battery by RELiON



Price: CAD \$799.00

SKU: RB40

Product Categories: Batteries, Lithium, Multi-Use: 12V, 20-99AHr, Shop

Product Tags: 12v, 40ahr, canada, rb40, rb40 canada, relion, relion battery, relion

rb40, relion rb40 canada

Product Page:

https://www.modernoutpost.com/product/rb40-40ahr-12v-lithium-battery-by-relion/

Product Summary

The RB40 is an efficient and fast-charging 12V 40ah lithium battery, powerful yet compact enough to fit in many deep cycle applications. The RB40 is a lithium iron phosphate (LiFePO4) battery with more power, less weight and up to 10x longer life than its lead-acid counterparts.

Product Description

The RB40 is an efficient and fast-charging 12V 40ah lithium battery, powerful yet

compact enough to fit in many deep cycle applications. The RB40 is a lithium iron phosphate (LiFePO4) battery with more power, less weight and up to 10x longer life than its lead-acid counterparts.

Lithium is the logical choice for applications that will exhaust the batteries or run in extreme weather. RELiON lithium batteries provide more energy for high consumption than traditional lead-acid batteries. Lead-acid batteries also need to be maintained. If they are not maintained properly, their life span is shortened. Because lithium batteries require no active maintenance, a one-time purchase guarantees better lifetime value.

The RB40 is suitable in many outdoor and recreation applications where lighter weight and capacity are key. It's commonly used in the following applications: fishing electronics, robotics, solar lighting, remote power, outdoor adventures, and other deep cycle applications.

RELiON lithium batteries provide more energy for high consumption than traditional lead-acid batteries. They also offer ultra-fast charging and discharging, high efficiency and a longer cycle life – plus no maintenance!

Not all lithium batteries are created equal. All RELiON Batteries use the safest and most stable components, including a LiFePO4 cathode and a built-in Battery Management System (BMS). The BMS ensures a long lifetime, safe handling – and high-accuracy State of Charge (SOC) calculations.

RB40 Specifications...

ELECTRICAL

Nominal Voltage: 12.8 V

Nominal Capacity: 40 Ah

Capacity @ 25A: 96 min

Energy: 512 Wh

Resistance : \leq 50 m Ω @ 50% SOC

Efficiency: 99%

Self Discharge : <3% per Month Maximum Modules in Series : 4

MECHANICAL

Dimensions (L x W x H): 197 x 166 x 173 mm (7.8 x 6.5 x 6.8")

Weight: 5.4 kg (12 lbs)

Terminal Type: M8

Case Material: ABS

Enclosure Protection: IP56

Cell Type : Cylindrical

Chemistry: LiFePO4

COMPLIANCE

Certifications : CE (battery)

UN38.3 (battery)

UL1642 & IEC62133 (cells)

Shipping Classification UN 3480, CLASS 9

Download the Full Spec Sheet]

Product Attributes

- Dimensions: 1 × 1 × 1 cm

- Weight: 5 kg