
S-5-S Metal Roof Attachment Clamp by S-5!



Price: CAD \$11.19 - CAD \$15.99

Product Categories: Metal Roof, Mounts, Rooftop Attachments, Shop

Product Tags: <u>s</u>, <u>s-5-s</u>, <u>s-5-s canada</u>, <u>s-5-s mini</u>, <u>s-5! canada</u>, <u>s5</u>, <u>s5-s</u>

Product Page:

https://www.modernoutpost.com/product/s-5-s-metal-roof-attachment-clamp-by-s-5

Product Variants

- Metal Roof Attachment Clamp by S-5! Standard ()
- S-5-S Metal Roof Attachment Clamp by S-5! Mini ()

Product Summary

The S-5-S clamp was created specifically for popular snap-together profiles

including residential profiles by Taylor Metals and Easy Lock Standing Seam. Its simple design and size make it

perfect for use with solar. Installation is as simple as setting the patented round-point

setscrews into the clamp, placing the clamp on the seam, and tightening them to the specified tension. Then, affix ancillary items using the M8 bolt provided with the product.

Product Description

The S-5-S clamp was created specifically for popular snap-together profiles including residential profiles by Taylor Metals and Easy Lock Standing Seam. Its simple design and size make it perfect for use with solar. Installation is as simple as setting the patented round-point setscrews into the clamp, placing the clamp on the seam, and tightening them to the specified tension. Then, affix ancillary items using the M8 bolt provided with the product.

The S-5-S and S-5-S Mini clamps are each furnished with set screws & M8 bolt hardware (standard model only). Each box also includes a bit tip for tightening setscrews using an electric screw gun. A structural aluminum attachment clamp, the S-5-S is compatible with most common metal roofing materials excluding copper. All included hardware is stainless steel.

The S-5-S clamp has been tested for load-to-failure results on most major brands and profiles of standing seam roofing. S-5!® holding strength is unmatched in the industry. Profiles that are shaped as illustrated below will work with the S-5-S and S-5-S Mini. In order for the S-5-S to fit these types of seams, the finished seam must:

- Be at least 1.00" high.
- Have a height distance less than or equal to 0.25" between the male portion of the panel and female portion of the panel.

S-5-S Mini Clamp

The S-5-S Mini is a bit shorter than the S-5-S and has one setscrew rather than two.

The mini is the choice for attaching all kinds of rooftop accessories: signs, walkways, satellite dishes, antennas, rooftop lighting, lightning protection systems, solar arrays, exhaust stack bracing, conduit, condensate lines, mechanical equipment—just about anything!

s-5-s clamps brochure s-5-s and mini installation

Product Attributes

Document Downloads

- Dimensions: N/A

- Model: Standard, Mini

Product Gallery



