

SEC-1230UL : 30A, 3-Stage Battery Charger by Samlex



Price: CAD \$459.00

SKU: SXSEC1230UL

Product Categories: [AC-DC Chargers : Lead Acid Batteries](#), [Battery Chargers](#), [Shop](#)

Product Tags: [1230ul](#), [12v](#), [12v battery](#), [2-bank](#), [3 stage](#), [3-bank](#), [3-stage battery charger](#), [30 amp](#), [30A](#), [battery charger](#), [canada](#), [samlex](#), [Samlex SEC-1230UL](#), [sec-1230ul](#), [system](#)

Product Page:

<https://www.modernoutpost.com/product/sec-1230ul-30a-3-stage-battery-charger-by-samlex/>

Product Summary

Protect your battery investment. Upgrade your basic converter to a Samlex SEC Smart Charger! The Samlex SEC-1230UL is an advanced fully automatic three-stage 30 Amp battery charger. Ideal for charging all types of 12 Volt lead-acid batteries (Flooded / Absorbed Glass Mat (AGM) / Gel Cell) from a 120 V, 60 Hz or 230 V, 50 Hz AC source.

Product Description

Protect your battery investment. Upgrade your basic converter to a Samlex SEC Smart Charger! The Samlex SEC-1230UL is an advanced fully automatic three-stage 30 Amp battery charger. Ideal for charging all types of 12 Volt lead-acid batteries (Flooded / Absorbed Glass Mat (AGM) / Gel Cell) from a 120 V, 60 Hz or 230 V, 50 Hz AC source.

Use utility power or a generator to rapidly charge & maintain your batteries.

Thousands of these chargers are in service worldwide. Certified to meet stringent UL standards.

By means of a DIP switch setting, conversion to a two-stage algorithm is possible to charge batteries connected to a DC load (DC UPS). The unit can also be used as a DC Power Supply.

Features include overload and short-circuit protection. The unit allows charging of up-to 3 separate battery banks...

SEC-1230UL Charger Features...

High efficiency

Commercial Grade

Lightweight

Quiet operation

Industry Proven Design - 1000s of units in operation

2 or 3 stage charging (user selectable)

120 or 230 VAC, 50/60 Hz (user selectable)

Voltage meter display - Ammeter and LED power status

For all types of Lead Acid batteries

Charge with a battery load or stand alone

Use as a power supply or DC UPS

UPC: Universal Protection Circuit - short circuit, overload, reverse battery polarity

Charge 3 banks of batteries at once - no isolator necessary

Specifications...

Input

120 VAC 60 Hz or 230 VAC 50 Hz

Output

12 VDC

Amps

30 Amps

Weight

7 (lbs)

Weight

3.17 (kg)

Dimensions

10.5 x 8.5 x 3 (in)

Dimensions

26.7 x 21.6 x 7.6 (cm)

Safety

Listed to UL Standard UL-1564, EMI Compliant to FCC Part 15(B), Class B

Warranty

2 Years (Canada/US)

Applications...

Automotive

Recreational vehicles

Marine

Communications sites

Battery back-up systems

Downloads...

[Manual](#)

[Spec Sheet](#)

Product Attributes

- Dimensions: 1 × 1 × 1 cm
- Weight: 4.2 kg

Product Gallery

