

SEC-2415UL : 15A, 24VDC 3-Stage Battery Charger by Samlex



Price: CAD \$459.00

SKU: SXSEC2415UL

Product Categories: [AC-DC Chargers : Lead Acid Batteries](#), [Battery Chargers](#), [Shop](#)

Product Tags: [15A](#), [2-bank](#), [2415](#), [2415ul](#), [24V](#), [24v battery](#), [3-bank](#), [battery charger](#), [canada](#), [samlex](#), [samlex charger](#), [samlex charger canada](#), [samlex sec charger](#), [Samlex SEC-2415UL](#), [samlex sec2415](#), [sec](#), [sec-2415ul](#), [sec-2415ul canada](#), [sec2415](#), [sec2415ul](#), [system](#)

Product Page:

<https://www.modernoutpost.com/product/sec-2415ul-15a-24vdc-3-stage-battery-charger-by-samlex/>

Product Summary

Protect your battery investment. Upgrade your basic converter to a Samlex SEC Smart Charger! The Samlex SEC-2415UL is an advanced, fully automatic, three-stage 15 Amp battery charger ideal for charging all types of 24 Volt lead-acid batteries (Flooded / Absorbed Glass Mat (AGM) / Gel Cell) from a 120 V, 60 Hz or 230 V, 50 Hz AC source.

Product Description

Protect your battery investment. Upgrade your basic converter to a Samlex SEC Smart Charger! The Samlex SEC-2415UL is an advanced, fully automatic, three-stage 15 Amp battery charger ideal for charging all types of 24 Volt lead-acid batteries (Flooded / Absorbed Glass Mat (AGM) / Gel Cell) from a 120 V, 60 Hz or 230 V, 50 Hz AC source.

Use utility power or a generator to rapidly charge & maintain your batteries.

Thousands of these chargers are in service worldwide. Certified to meet stringent UL standards.

By means of a DIP switch setting, conversion to a two-stage algorithm is possible to charge batteries connected to a DC load (DC UPS). The unit can also be used as a DC Power Supply.

Features include overload, short-circuit and over-temperature protection. The SEC-2415UL unit allows charging of up-to 3 separate battery banks.

SEC-2415UL Features...

High efficiency

Commercial Grade

Lightweight

Quiet operation

Industry Proven Design – 1000s of units in operation

2 or 3 stage charging (user selectable)

120 or 230 VAC, 50/60 Hz (user selectable)

Voltage meter display – Ammeter and LED power status

For all types of Lead Acid batteries

Charge with a battery load or stand alone

Use as a power supply or DC UPS

UPC: Universal Protection Circuit – short circuit, overload, reverse battery polarity

Charge 3 banks of batteries at once – no isolator necessary

SEC-2415UL Specifications...

Input

120 VAC or 230 VAC

Output

24 VDC

Amps

15 Amps

Remote Control

900-RC

Weight

6 (lbs)

Weight

2.72 (kg)

Dimensions

10.5 x 8.5 x 3 (in)

Dimensions

26.7 x 21.6 x 7.6 (cm)

Safety

Listed to UL Standard UL-1564, EMI Compliant to FCC Part 15(B), Class B

Warranty

2 Years (Canada/US)

Applications...

Automotive

Recreational vehicles

Marine

Communications sites

Battery back-up systems

Downloads...

Manual

Spec Sheet

Product Attributes

- Dimensions: 1 × 1 × 1 cm
- Weight: 3.9 kg

Product Gallery

