

## SolaDeck 0766-41 AD : Rooftop PV Combiner (Tile Roof)



Price: CAD \$395.00

**SKU:** SD076641AD

**Product Categories:** [Shop](#), [Combiners: Solar & Battery](#), [Wiring & BOS](#)

**Product Tags:** [array combiner](#), [canada](#), [combiner](#), [pv combiner](#), [roof](#), [rooftop](#), [sd-0766-41](#), [sd-0766-41 ad](#), [soladeck](#), [soladeck 0766-41](#), [soladeck canada](#), [soladeck combiner](#)

**Product Page:**

<https://www.modernoutpost.com/product/soladeck-0766-41-ad-pv-combiner-tile/>

### Product Summary

SolaDeck 0766-41 AD rooftop combiner enclosure. AC/DC. Includes bump lid to accommodate breakers.

**SPECIAL-ORDER ITEM** - Allow 2-3 weeks for delivery.

### Product Description

SolaDeck 0766-41 AD rooftop combiner enclosure with additional depth for use on tile roofs.

AC/DC.

Includes bump lid to accommodate breakers.

7" DIN rail length.

**SPECIAL-ORDER ITEM** - Allow 2-3 weeks for delivery.

SolaDeck SD-0766-41 AD Features...

Brand

SOLADECK

Manufacturer Part Number

0766-41 AD

Warranty

1-year

NEMA Rating

NEMA 3

Deadfront (Y/N)

No

Length

16.0

Width

16.0

## Height

8.0

## Weight

9.0 LB

## Volume

2048.0 CIN

## Why Use A SolaDeck Enclosure?

As the desire to utilize solar energy grows, so does the need for a convenient, virtually unnoticeable enclosure to penetrate the roof deck. SolaDeck both houses and protects the solar PV wiring for a fast, easy, and safe photovoltaic wire installation.

Solar panel wiring can be installed with consistency, time savings, and confidence every time. Unlike other solar array wiring enclosures, SolaDeck incorporates a unique flashing that is a seamless part of the enclosure and prevents incorrect penetrations in the roof system.

SolaDeck 0766-41 AD Enclosure/Combiners Provide...

Flashed, seamless, weather-tight roof protection

Roof penetration standard in the roofing industry

Exceptional low profile design

Versatility to all PV systems

Consistency in every installation

A professional appearance to your PV installation

Models that are ETL listed and labeled to UL standards

## Product Attributes

- Dimensions: 1 &times; 1 &times; 1 cm
- Weight: 4 kg

## Product Gallery

