Venture 75 USB Power Pack from Goal Zero



CAD \$159.00][200,200,200][14]

Current Sale Price: Original price was: CAD \$159.00.CAD \$99.00Current price is: CAD \$99.00.

SKU: GZVENTURE-75

Product Categories: <u>Batteries</u>, <u>Bike Touring</u>, <u>Kayak & Canoe Solar</u>, <u>Lithium</u>, <u>On</u> <u>The Road</u>, <u>On The Trail</u>, <u>On The Water</u>, <u>Packable USB Battery Packs</u>, <u>Rugged Stuff</u>, <u>Shop</u>, <u>Specials</u>

Product Tags: <u>22110</u>, <u>canada</u>, <u>goal zero 22110 canada</u>, <u>goal zero venture 75</u>, <u>solar battery</u>, <u>solar usb battery</u>, <u>usb battery pack</u>, <u>usb-c</u>, <u>usbc</u>, <u>venture 75</u>, <u>venture</u> <u>75 canada</u>

Product Page:

https://www.modernoutpost.com/product/venture-75-usb-power-pack-from-goal-zer o/

Product Summary

Trust Goal Zero to make a battery as tough as this one. The Venture 75 packs 75Wh of energy for all your USB devices, in an IP67 dustproof/waterproof casing. The USB-C port is designed to speed up charging and streamline cable carry. Power up tablets, laptops, and other USB-C devices using the 60W USB-C Power Delivery port, then use the same port to quickly recharge the power bank in 1.5 hours. Ideal for outdoor recreation, travel, and emergency use.

Product Description

Trust Goal Zero to make a battery as tough as this one. The Venture 75 packs 75Wh of energy for all your USB devices, in an IP67 dustproof/waterproof casing. The USB-C port is designed to speed up charging and streamline cable carry. Power up tablets, laptops, and other USB-C devices using the 60W USB-C Power Delivery port, then use the same port to quickly recharge the power bank in 1.5 hours. Ideal for outdoor recreation, travel, and emergency use.

Venture 75 Features...

IP67 rating

Ensures protection against dust, sand and debris, and can withstand submersion up to 1 meter of water for at least 30 minutes

New 60W USB-C Power Delivery port

Provides high-speed charging in and out

Fresh design

Features a protective rubber sleeve and a waterproof plug that protects your ports against the elements when not in use

Integrated 50 lumens emergency flashlight Lights up trails or hallways in a pinch Product data have been exported from - <u>Modern Outpost</u> Export date: Mon Nov 25 17:57:45 2024 / +0000 GMT

Charging the Venture 75

The Venture 75 can be recharged from a USB-C power delivery source in as little as 1.5 hours.

Recharge the Venture 75 from the sun by connecting a compatible solar panel in about 6 hours.

We recommend the **Nomad 50** or <u>Nomad 20</u>] for the best charging experience.

Powering Your Devices

The Venture 75 is great for all of your USB powered devices.

With just the onboard energy reserve, you have the following capability...

- Smartphone: 5 Recharges - POV Camera: 14 Recharges - Headlamp: 14

Recharges - Tablet: 2 Recharges - USB-C Laptops: Up to 1 Recharge Add solar input to extend your charging options, and do more.

NOTE: This is NOT like your typical USB battery banks. The Venture 75, like all batteries designed to work with solar (if/when needed), it will accept charge at the same time it delivers charge. This "pass-through" charging capability is the mark of a superior battery bank, and a feature that distinguishes great batteries from ordinary.

Venture 75 Specifications

BATTERY DETAILS

Cell chemistry: Li-ion NMC Cell type: 18650 by LG chem Cell capacity: 71.04Wh (11.1V, 6400mAh) Single Cell Equivalent Capacity: 19200mAh @ 3.7V Pack Lithium Content: 5.76g Lifecycles: Hundreds of cycles Shelf-life: Charge every 3-6 months Fuses: None Management system: Charging and low-battery protection built-in

PORTS

USB-A port (output): 5V, up to 3A each (15W max), regulated USB-C port (input/output): 5-20V, up to 3A (60W max), regulated

LIGHT

LED (output): 50 Lumens, white LED

CHARGE TIMES

USB-C PD (60W): 1.5 Hours Wall Charger (45W) USB-C: 2 Hours USB-A (2.4A): 6 Hours Nomad 10: 11-22 Hours Nomad 20: 6-11 Hours Nomad 20: 6 hours **GENERAL** Product SKU: 22110 IP Rating: IP67 Chainable: No Weight: 20.35oz (577g) Dimensions: 6.1 x 3.8 x 1.1 in (15.6 x 9.6 x 2.9 cm) Operating usage temp.: 32-113F (0-45C) Certs: CE< FCC, RoHS Warranty: 12 months

Product Attributes

- Dimensions: 16 × 10 × 3 cm
- Weight: .6 kg

Product Gallery





